

Grading Pich Approved as shown and/or noted THOMAS P. GILLES, P.E. Lake County Engineer 425

B

ROOF DRAINS
SHALL DISCHARGE
TO SPLASH BLOCKS



GENERAL NOTES:

I. DRIVEWAY APRON TO BE 6" THICK
2. BENCHMARK - TOP STEM OF FIRE HYDRANT LOCATED IN FRONT OF SUBLOT NO. 36, ELEV.= 674.10

LEGEND



PROPOSED CONTOUR

100.00 00.00

PROPOSED ELEVATION

CERTIFICATION

"I THE UNDERSIGNED HEREBY CERTIFY THAT THIS TOPOGRAPHY INDICATED BY I' CONTOURS AND ELEVATIONS SHOWN HEREON REPRESENTS AN ACTUAL SURVEY MADE BY ME ON THE 30th DAY OF JAN , 1992 AND THE ELEVATIONS WERE TAKEN AT APPROPRIATE INTERVALS AND AS OF THAT DAY THEY EXISTED AS INDICATED HEREON.

"I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME AND IS CORRECT TO THE BEST OF MY KNOWLEDGE" /

THENTIN S. HIMEBAUGH, P.S. No. 68820

PREPARED BY:

Himebaughand Novak

Surveyors and Site Consultants 38083 West Spaulding St. Willoughby, Ohio 44094 (216) 946-1761

SUBLOT No. 6, GREENSIDE DRIVE, PAINESVILLE ASHBOURNE SUBDIVISION, VOL. 12, PG. 4
SCHOENIGER BROS. CONSTRUCTION INC.
|" = 20'

TWP., OH

PLAN:

BΥ:

DECEMBER 17, 1993 DAVID W. NOVAK